

FLAGPOLE TRUCKS & ACCESSORIES



For External Halyard Poles • Cap Style • Stationary • Single Pulley

ST-1 SERIES

- **Construction:** cast aluminum
 - **Pulley:** 1" outside diameter cast nylon on 3/16" stainless steel axle
 - **Max halyard diameter:** 1/4"
 - **Truck:** secured by 1 stainless steel set screw (size 1/4"-20NC)
 - **Ornaments:** accepts spindle threading of 1/2"-13NC.* Secured by 1 stainless steel pan head screw (size 10-32)
- * Can be supplied with other threading sizes if desired

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
ST-1-38	1-3/8"	1.0	340000	\$25.00	\$23.00	340005	\$28.50	\$26.00	340010	\$28.50	\$26.00	340015	\$28.50	\$26.00
ST-1-12	1-1/2"	1.0	340001	25.00	23.00	340006	28.50	26.00	340011	28.50	26.00	340016	28.50	26.00
ST-1-34	1-3/4"	1.0	340002	25.00	23.00	340007	28.50	26.00	340012	28.50	26.00	340017	28.50	26.00
ST-1-16	1-15/16"	.80	340003	25.00	23.00	340008	28.50	26.00	340013	28.50	26.00	340018	28.50	26.00
ST-1-20	2"	.80	340004	25.00	23.00	340009	28.50	26.00	340014	28.50	26.00	340019	28.50	26.00



For External Halyard Poles • Cap Style • Stationary • Double Pulley

ST-32 SERIES

- **Construction:** cast aluminum
 - **Pulleys:** 1-1/2" outside diameter cast nylon on 1/4" stainless steel axles
 - **Max halyard diameter:** 5/16"
 - **Truck:** secured by 3 stainless steel set screws (size 5/16"-18NC)
 - **Ornaments:** accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel set screw (1/4"-20NC)
- * Can be supplied with other threading sizes if desired

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
ST-3	1-7/8"	1.9	340040	\$51	\$46	340042	\$55	\$51	340044	\$55	\$51	340046	\$55	\$51
ST-2	2-3/8"	1.7	340041	51	46	340043	55	51	340045	55	51	340047	55	51



For External Halyard Poles • Cap Style • Stationary • Single Pulley

OT SERIES

- **Construction:** cast aluminum
 - **Pulley:** cast nylon on 1/4" stainless steel axle (1-1/2" outside diameter on OTH, OT1, OT25, OT35; 2" on OT2, OT3, OT325)
 - **Max halyard diameter:** 5/16"
 - **Truck:** secured by stainless steel set screws (one 1/4"-20NC on OTH; three 5/16"-18NC on OT1, OT2, OT25, OT3, OT325, OT35)
 - **Ornaments:** accepts spindle threading of 1/2"-13NC.* Secured by 1 stainless steel pan head screw (size 10-32)
- * Can be supplied with other threading sizes if desired

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
OTH	2"	.55	340056	\$23.00	\$21.00	340062	\$26.00	\$24.00	340068	\$26.00	\$24.00	340074	\$26.00	\$24.00
OT1	2-3/8"	.95	340057	31.50	26.00	340063	35.00	31.00	340069	35.00	31.00	340075	35.00	31.00
OT25	2-1/2"	.95	340058	33.00	28.50	340064	39.00	33.00	340070	39.00	33.00	340076	39.00	33.00
OT2	2-3/4"	1.5	340059	35.00	30.50	340065	40.00	35.00	340071	40.00	35.00	340077	40.00	35.00
OT3	3"	1.3	340060	39.00	33.00	340066	42.00	39.00	340072	42.00	39.00	340078	42.00	39.00
OT325	3-1/4"	1.2	340343	40.00	34.00	340344	45.00	42.00	340345	45.00	42.00	340346	45.00	42.00
OT35	3-1/2"	1.8	340061	43.00	40.00	340067	46.00	43.00	340073	46.00	43.00	340079	46.00	43.00



For External Halyard Poles • Cap Style • Revolving • Single Pulley

RTC-1 SERIES

- **Construction:** cast aluminum
 - **Pulley:** 1-1/2" outside diameter cast nylon on 1/4" stainless steel axle
 - **Max halyard diameter:** 5/16"
 - **Truck:** secured by 3 stainless steel set screws (1/4"-20NC on RTC-1-2, RTC-1-138; 5/16"-18NC on RTC-1-238)
 - **Ornaments:** accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel set screw (1/4"-20NC)
 - **Movement:** utilizes self-lubricating ball bearing assemblies for ease of rotation, product life and strength
- * Can be supplied with other threading sizes if desired

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTC-1-138	1-3/8"	1.8	340351	\$87	\$76	340308	\$96	\$86	340309	\$96	\$86	340352	\$96	\$86
RTC-1-2	2"	1.6	340104	87	76	340106	96	86	340108	96	86	340110	96	86
RTC-1-238	2-3/8"	1.9	340105	87	76	340107	96	86	340109	96	86	340111	96	86