

For External Halyard Poles • Threaded • Revolving • Double Pulley

EXTRA HEAVY-DUTY SERIES

IH-1 SERIES

IH-2 SERIES

- Construction: cast aluminum
- Pulleys: 3-7/8" outside diameter cast aluminum on 1/2" stainless steel axles
- Max Halyard Diameter: 3/8"
- Truck Spindle: 1-1/4" NPT threading
- Flagpole: For up to 12-3/4" outside top diameter pole w/ female fitting installed
- Ornaments: accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel set screw (1/4"-20NC)
- Movement: utilizes stainless steel sealed lubricant ball bearing assemblies for ease of rotation, product life and strength
- * Can be supplied with other threading sizes if desired

	SPINDLE		SILVER			BF	RONZE #3	13		WHITE		BLACK		
MODEL	MATERIAL	LBS.	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+
XHDT	ALUMINUM	9.7	340160	\$680	\$610	340162	\$715	\$645	340164	\$715	\$645	340166	\$715	\$645
XHDT-SS	STAINLESS STEEL	12	340161	1,310	1,180	340163	1,335	1,205	340165	1,335	1,205	340167	1,335	1,205



For Rope Style Internal Halyard Poles Cap Style • Stationary • Single Pulley

- Construction: cast aluminum
- Internal Pulley: 1-1/2" outside diameter cast nylon on 1/4" stainless steel axle. Pulley assembly affixed to inside of truck by 5/16"-18NC stainless steel set screw
- External pulley: cast nylon on 1/4" stainless steel axle (2" outside diameter on IH-1-3; 1-1/2" on IH-1-35)
- Max halyard diameter: 5/16"
- Truck: secured by 3 stainless steel set screws (size 5/16"-18NC)
- Ornaments: accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel pan head screw (size 10-32)
- * Can be supplied with other threading sizes if desired

	FITS POLE		SILVER			BRONZE #313				WHITE		BLACK			
MODEL	DIAMETER	LBS.	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+	
IH-1-3	3"	1.6	340178	\$59	\$54	340180	\$66	\$59	340182	\$66	\$59	340184	\$66	\$59	
IH-1-35	3-1/2"	2.3	340179	77	71	340181	90	79	340183	90	79	340185	90	79	







For Cable Style Internal Halyard Poles Threaded • Revolving • Single Pulley

- Construction: cast aluminum
- · Cable Bushing: IHT-3 has a bronze fitting; all other sizes supplied with a stainless steel bushing at the cable exit
- Truck Spindle: 1-1/4" NPT threading
- · Ornaments: accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel
- set screw (1/4"-20NC)
 - Movement: IHT-3 utilizes stainless steel sealed lubricant bearing assemblies; all other sizes utilize enclosed stainless steel bearings and raceway.
 - * Can be supplied with other threading sizes if desired

	TRUCK BASE	TRUCK	MAX. POLE		SILVER			BRONZE #313			WHITE			BLACK		
MODEL	DIA.	HT.	TOP DIA.	LBS.	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+
IHT-VR	5"	4-1/2"	3"	3.3	340194	\$200	\$182	340198	\$220	\$200	340206	\$220	\$200	340202	\$220	\$200
IHT-1	6-1/2"	6-1/2"	4"	6.4	340195	300	270	340199	326	294	340207	326	294	340203	326	294
IHT-2	7-1/2"	7-1/4"	5"	8.1	340196	362	325	340200	394	354	340208	394	354	340204	394	354
IHT-3	10-1/2"	8-1/2"	7-1/2"	16	340197	708	638	340201	785	706	340209	785	706	340205	785	706



Recommended: Thread halyard to inside of halyard pin stop as shown.



· Construction: cast aluminum

- Internal Pulley: 2" outside diameter cast nylon on 1/4" stainless steel axle. Pulley assembly affixed to inside of truck
- Max halyard diameter: 5/16"
- Truck Spindle: 1-1/4" NPT threading
- **IHT-VS SERIES**
 - Flagpole: For up to 3-1/2" outside top diameter pole w/ female fitting installed
 - Ornaments: accepts spindle threading of 1/2"-13NC*. Secured by 1 stainless steel set screw (1/4"-20NC)
 - * Can be supplied with other threading sizes if desired

For Rope Style Internal Halyard Poles • Threaded • Stationary • Single Pulley

	FITS POLE	SILVER			BRONZE #313				WHITE		BLACK			
MODEL	DIAMETER	LBS.	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+	ITEM#	1-5	6+
IHT-VS	3-1/2"	2.4	340312	\$78	\$70	340313	\$87	\$78	340314	\$87	\$78	340315	\$87	\$78